
Squaresert® GK08







English	Français	Deutsch	Italiano	Español
Square section	Corps carré	Vierkantschaft	Corpo quadrati	Cuerpo quadrado
Large flange	A collerette	Flachkopf	Flangiato	Ala Ancha
Low carbon steel*	Acier bas carbone*	Stahl*	Acciaio a basso tenore di carbonio*	Acero bajo en carbono*
Zinc plated, thickness 10µm Clear trivalent passivated	Revêtement zingué, épaisseur 10 µm Passivation claire trivalente	Verzinkt, 10 µm Klar chromatiert, Cr6-frei	Zincatura spessore 10µm Passivazione chiara trivalente	Zincado, 10 micras Pasivado claro trivalente

* : QSt 34-3, EN10016-2



ø	e (grip) min.	e (grip) max.	A/F ±0.1	A max.	B max.	D max.	J max.	M max.	P max.	Part No/ref
M5 x 0.8	0.50	1.50	7.30	7.10	10.90	0.65	10.40	11.40	8.20	0GK08-72514
	1.50	3.00						13.00		0GK08-72516
M6 x 1.0	0.50	2.00	9.30	9.10	13.50	0.95	13.50	15.50	9.90	0GK08-72619
	2.00	4.00						17.50		0GK08-72622
M8 x 1.25	1.00	3.00	11.30	11.10	18.00	1.65	16.40	18.90	11.80	0GK08-72823

all dimensions in mm / en millimètres / alle Maße in mm / in millimetri / en milimetros

				
	Recommended max. torque	Pull-out	Torque-to-turn	Push-out
ø	Nm max.	kN	Nm min.	kN
M5 x 0.8	7.9	5.5	10.2	2.4
M6 x 1.0	12.4	7.3	15.4	4.6
M8 x 1.25	32.0	10.5	34.0	6.5

Avdel®

An Acument™ Global Technologies Company

www.avdel-global.com

© 2007 Acument Intellectual Properties, LLC

Squaresert® is a trademark of Avdel UK Limited

04.2007

Data shown is subject to change without prior notice as a result of continuous product development and improvement policy.
Your local Avdel representative is at your disposal should you need to confirm latest information.