

Briv® 1802




English	Français	Deutsch	Italiano	Español
120° Countersunk	120° Tête fraisée	120° Senkkopf	120° Testa svasata	120° Cabeza avellanada
Aluminium alloy* (5 % Mg) Natural	Alliage d'aluminium* (5% Mg) Brut	Aluminium* (5 % Mg) Blank	Lega di alluminio* (5% Mg) Nessuna finitura	Aluminio* (5% Mg) Natural

*: BS 1473 5056A DIN 1725 AlMg5 Werkstoff 3.3555







Rec. c/sunk hole dimensions (ø 3.2 mm only)
Dimensions recommandées du trou fraisé (3,2 mm seulement)
Empf. Abmessungen für Senkloch (nur ø 3,2 mm)
Dimensioni raccomandate del foro svasato (solo 3.2).
Dimensiones del taladro avellanado recomendadas (solo 3.2)

ø					A	B	C	D			Fasteners per pod /Nombre de rivets par chargeur / Niete pro Magazin / Rivetti per caricatore / Uds./carga	Part No/ref
nom.	min.	max.	min.	max.	± 0.5	max.	max.	max.	kN[1]	kN[1]	± 1	
3.2 (1/8")	1.52	2.79	3.26	3.34	5.5	0.89	4.77	3.17	0.7	1.3	64	01802-00406
	2.54	3.81					5.79				52	01802-00407
	3.56	4.83					6.81				44	01802-00408
	4.57	5.84					7.82				38	01802-00410
	5.59	6.86					8.84				33	01802-00411
4,0 (5/32")	1.57	2.93	3.97	4.04	6.5	1.02	5.18	3.90	1.1	1.7	59	01802-00505
	2.15	3.43					5.69				54	01802-00506
	2.66	3.94					6.19				49	01802-00507
	3.68	4.96					7.21				42	01802-00509
	4.69	5.97					8.22				36	01802-00511
	5.71	6.99					9.24				32	01802-00513

all dimensions in mm / en millimètres / alle Maße in mm / in millimetri / en milimetros

1) typical values / valeurs moyennes / typische Werte / Valori tipici / resistencias máximas recomendadas

Avdel®
An Acument™ Global Technologies Company

www.avdel-global.com

© 2007 Acument Intellectual Properties, LLC

Briv® is a trademark of Avdel UK Limited

02.2007

Data shown is subject to change without prior notice as a result of continuous product development and improvement policy.
Your local Avdel representative is at your disposal should you need to confirm latest information.